

Smarter technology for all

Lenovo Update on IBM Storage Scale

Sigrun Eggerling | March 2024

Lenovo

Partnership solutions

- Lenovo partners with leading storage solution partners
- Software defined storage running on Lenovo hardware
- Lenovo HPC solutions with partner hardware
- Lenovo EveryScale
 - Solutions
 - Design Architectures



Lenovo DSS-G

Based on IBM Storage Scale




2024 Lenovo. All rights reserved.



Over a decade of DSS-G heritage

Delivering continuous solution innovation



Solution support ends December 2022

Solution support until at least March 2027

Solution support until at least mid 2029

Lenovo HPC Storage portfolio

Lenovo DSS-G

DSS-G 2xy



IBM
Storage
Scale RAID



DSS-G 100
Erasure Code Edition


DSS-G-NVX2



IBM
Storage
Scale



DDN EXAScaler



Lenovo Server Series



Lenovo DE Series



IBM
Spectrum
Scale





DSS-G Naming



Lenovo DSS-G (Gen5) Configurations (Genoa)


There are 12 homogeneous and 13 mixed model numbers for JBOD configurations:

Next DSS-G2XX next is based on AMD Genoa based system.
External SAS adapter is 24Gbit SAS PCIe Gen4. Due to PCI limitations, max 4 SAS adapters supported.



There is only one model number for ECE: DSS-G100.

But a Lenovo ECE solution will consist of multiple ECE servers where each one will be configured with at least 6 but not more than 32 servers. Storage solutions can be a hybrid mix of DSS-G and ECE Here are 3 examples.



Phase 1 2/29

Phase 2 4/12

(Planned)

Footnotes:

1. Fits in 48U rack.
2. Requires 2 racks.

DSS-G2xy Components



ThinkSystem SR655 V3 servers

Two ThinkSystem SR655 V3 servers act as NSD/IO server, each powered by a single AMD Genoa CPU and up to 768GB RAM. Choice of single port NDR or dual port NDR-200 VPI adapter (Ethernet capable).



D4390 spinning disk storage

With up to eight enclosures, the D4390 is a 4U JBOD with 90 spinning enterprise-ready NL-SAS hard drive, supporting 12-22TB configurations.



D1224 SAS-SSD storage

With up to four enclosures, the D1224 is a 2U SAS-SSD JBOD with up to 24 drives. Can be combined in a hybrid or all flash configuration.




Engineered solution

A fully validated software stack with all Red Hat Enterprise and IBM Storage Scale licenses. Available full factory integrated.


DSS-G is a fully integrated EveryScale solution to support HPC/AI workloads

Available with Premier Support

Why Lenovo DSS-G?




DSS-G220 – SR655 V3 + D4390



OCP Options:
2x 10G Base-T
4x 10G Base-T
2x 10/25Gb SFP28
4x 10/25Gb SFP28
2x 100Gb QSFP+ (planned)

- 178 Enterprise NL-SAS HDD
- Single socket AMD Genoa system
 - Single vs dual socket under evaluation
 - Min 384GB RAM
- 4x SAS Adapters (PCIe Gen4)
- Networking options (PCIe Gen5)
 - 2x NVIDIA NDR adapters
 - 2x NVIDIA NDR-200 2 port adapters

D4390 Service Features



Smarter
technology
for all

Lenovo

thanks.